



# LEICA ULTRAVID BL 25 mm

## Technical Data



<b>Binocular</b>	<b>LEICA ULTRAVID 10 x 25 BL</b>
<b>Order No. Product</b>	
<b>Rubber armored, black</b>	40 253
<b>Delivery scope</b>	Woven carrying strap, eyepiece cover, deep-drawn leather case
<b>Magnification</b>	10 x
<b>Front lens diameter</b>	25 mm
<b>Exit pupil</b>	2.5 mm
<b>Twilight factor</b>	15.8
<b>Field of view at 1,000 m</b>	90 m
<b>Field of view at 1,000 yds</b>	273 ft
<b>Eye-relief</b>	15 mm
<b>Objective angle of view</b>	5.2°
<b>Close focusing distance</b>	approx. 3.2 m / 10.5 ft
<b>Diopter compensation</b>	± 3.5 diopters
<b>Automatic diopter compensation ADC™</b>	yes
<b>Eyepieces for eyeglass wearers</b>	yes
<b>Adjustable interpupillary distance</b>	34–74 mm
<b>Focusing</b>	Internal focusing via central focusing knob
<b>No. of lens elements (each side)</b>	6, all with HDC™ coating
<b>Prism system</b>	Roof prism with phase correcting coating P40 and HighLux-System HLS™
<b>Watertightness</b>	Watertight to a depth of 5 m / 16.5 ft
<b>Housing</b>	Aluminum, nitrogen-filled
<b>Dimensions (W x H x D)</b>	111 x 112 x 39 mm 4 3/8 x 4 3/8 x 1 1/2 in
<b>Weight</b>	approx. 255 g / 9 oz